



	6 X 6 FRONTIER 480	6 X 6 FRONTIER 580	6 X 6 FRONTIER 650	8 X 8 FRONTIER 650	8 X 8 AVENGER 700	8 X 8 AVENGER 750 EFI	8 X 8 750 HDi
ENGINE	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter						
	2 year warranty	2 year warranty	2 year warranty	2 year warranty	3 year warranty	3 year warranty	3 year warranty
MODEL	Briggs & Stratton Vanguard	Briggs & Stratton Vanguard	Briggs & Stratton Vanguard	Briggs & Stratton Vanguard	Kohler Aegis LH 690	Kohler Aegis LH 775	Kohler Aegis LH 775
HORSEPOWER	14	18	23	23	26	31	31
DISPLACEMENT	480cc	570cc	627cc	627cc	674cc	748cc	748cc
COOLING	Air Cooled	Air Cooled	Air Cooled	Air Cooled	Liquid Cooled	Liquid Cooled	Liquid Cooled
STARTING	Electric/Recoil	Electric/Recoil	Electric/Recoil	Electric/Recoil	Electric	Electric	Electric
BRAKES	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
STEERING	One-piece ergonomic handlebar steering control with mounted brake lever. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.						
CONTROLS	Right-hand twist grip throttle and dash-mounted choke control (Except Avenger 750 EFI and 750 HDi). Light switch and ignition switch.						
CLUTCH	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.						
TRANSMISSION	Planetary differential transmission with High and Low range; Forward, Neutral, Reverse.						ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.
DRIVE SYSTEM	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greaseable.						
FRAME	Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection.						
BODY	Vacuum formed High Molecular Weight Polyethylene						
FULL SKID PLATE	Optional	Optional	Standard	Optional	Standard	Standard	Standard
LOAD CAPACITY¹	ON LAND						
	700 lbs / 317 kg total	700 lbs / 317 kg total	700 lbs / 317 kg total	1000 lbs / 454 kg total	1150 lbs / 521 kg total	1150 lbs / 521 kg total	1150 lbs / 521 kg total
	140 lbs / 63 kg max.	140 lbs / 63 kg max.	140 lbs / 63 kg max.	no restrictions	no restrictions	no restrictions	no restrictions
	REAR COMPARTMENT						
	500 lbs / 227 kg total	500 lbs / 227 kg total	500 lbs / 227 kg total	900 lbs / 408 kg total	1000 lbs / 454 kg total	1000 lbs / 454 kg total	1000 lbs / 454 kg total
	ON WATER						
TOWING CAPACITY²	1200 lbs / 545 kg	1200 lbs / 545 kg	1400 lbs / 635 kg	1400 lbs / 635 kg	1800 lbs / 818 kg	1800 lbs / 818 kg	1800 lbs / 818 kg
SEATING CAPACITY³	ON LAND						
	4 persons	4 persons	4 persons	6 persons	6 persons	6 persons	6 persons
	ON WATER						
	2 persons	2 persons	2 persons	4 persons	4 persons	4 persons	4 persons
FUEL CAPACITY	7.1 US gallons (27 litres) See-through polyethylene fuel tank. 8 hours of operation ⁴						
SPEED⁵	ON LAND						
	22 mph / 35 km per hour	22 mph / 35 km per hour	22 mph / 35 km per hour	19 mph / 30 km per hour	20 mph / 32 km per hour	20 mph / 32 km per hour	20 mph / 32 km per hour
	ON WATER ⁴						
	3.5 mph / 5 km per hour	3.5 mph / 5 km per hour	3.5 mph / 5 km per hour	2.5 mph / 4 km per hour	2.5 mph / 4 km per hour	2.5 mph / 4 km per hour	2.5 mph / 4 km per hour
SHIPPING WEIGHT	850 lbs / 386 kg	850 lbs / 386 kg	890 lbs / 404 kg	1050 lbs / 476 kg	1250 lbs / 570 kg	1250 lbs / 570 kg	1250 lbs / 570 kg
AXLE BEARING EXTENSIONS	Front - N/A Rear - N/A	Front - Optional Rear - N/A	Front - Standard Rear - Standard	Front - Standard Rear - Optional	Front - Standard Rear - Standard	Front - Standard Rear - Standard	Front - Standard Rear - Standard
LCD DIGITAL GAUGE CLUSTER	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights				Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Engine Coolant Temperature, Low Oil Pressure and Parking Brake Reminder Lights (Avenger 750 EFI and 750 HDi also feature a Check Engine Light)		
TIRES	ARGO AT189 24x10.00-8NHS					ARGO AT189 25x12.00-9 NHS	
GROUND PRESSURE	2.1 psi (14.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks						
GROUND CLEARANCE	TIRES						
	9.5" (240 mm)	9.5" (240 mm)	9.5" (240 mm)	9" (230 mm)	9.5" (240 mm)	9.5" (240 mm)	9.5" (240 mm)
	TRACKS						
	10.5" (265 mm)	10.5" (265 mm)	10.5" (265 mm)	10" (255 mm)	10.5" (265 mm)	10.5" (265 mm)	10.5" (265 mm)
OPERATING CONDITIONS	All weather, all terrain, -40°C to +40°C						

- Capacity includes occupants, cargo, outboard motor and fuel, and installed accessories. Max. outboard motor size 7.4 kW (9.9 hp).
- Towing capacity is approximate and depends on type of surface, load on vehicle as well as incline. Max Hitch Tongue Load (when equipped with hitch) 100 lbs / 45kg for all models
- Subject to rear compartment load capacity limitations.
- Fuel consumption depends on load and operating conditions.
- All speeds are approximate and depend on conditions.
- Always wear approved Personal Floatation Device (PFD) when operating in water or on ice.

AVAILABLE ARGO COLORS



Tundra



Yellow



Black



Blue



Red



Realtree Hardwoods Green HD®



Shadow Branch®

*Colors in this brochure are reproduced with great care, but may vary slightly from actual ARGO vehicle colors.

Appearance and specifications subject to change without notice.