



	6 X 6 FRONTIER 580	6 X 6 650 HD	8 X 8 FRONTIER 650	8 X 8 700 HD	8 X 8 750 HDi	8 X 8 750 HDi SE
ENGINE	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter					
	2 year warranty	2 year warranty	2 year warranty	3 year warranty	3 year warranty	
MODEL	Briggs & Stratton Vanguard	Briggs & Stratton Vanguard	Briggs & Stratton Vanguard	Kohler Aegis LH 690	Kohler Aegis LH 775	
HORSEPOWER	18	23	23	26	31	
DISPLACEMENT	570cc	627cc	627cc	674cc	748cc	
COOLING	Air Cooled	Air Cooled	Air Cooled	Liquid Cooled	Liquid Cooled	
STARTING	Electric/Recoil	Electric/Recoil	Electric/Recoil	Electric	Electric	
BRAKES	Mechanical	Hydraulic	Mechanical	Hydraulic	Hydraulic	
STEERING	One-piece ergonomic handlebar steering control with hand brake. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.					
CONTROLS	Right-hand twist grip throttle and dash-mounted choke control (Except ARGO 8x8 750 HDi). Light switch and ignition switch.					
CLUTCH	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.					
TRANSMISSION	Planetary differential transmission with High and Low range; Forward, Neutral, Reverse.	ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.	Planetary differential transmission with High and Low range; Forward, Neutral, Reverse.	ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.	ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.	
DRIVE SYSTEM	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles and are protected with triple-sealed outer flange assemblies. Bearings are greaseable.					
FRAME	Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection.					
BODY	Vacuum formed High Molecular Weight Polyethylene					
FULL SKID PLATE	Optional	Standard	Optional	Standard	Standard	
LOAD CAPACITY¹	700 lbs / 317 kg total ²		1000 lbs / 454 kg total		1150 lbs / 521 kg total	
ON LAND	140 lbs / 63 kg max.		140 lbs / 63 kg max.		140 lbs / 63 kg max.	
REAR COMPARTMENT	500 lbs / 227 kg total		900 lbs / 408 kg total		1000 lbs / 454 kg total	
ON WATER	500 lbs / 227 kg total		900 lbs / 408 kg total		1000 lbs / 454 kg total	
TOWING CAPACITY³	1200 lbs / 545 kg	1400 lbs / 635 kg	1400 lbs / 635 kg	1800 lbs / 818 kg	1800 lbs / 818 kg	
SEATING CAPACITY⁴	4 persons		6 persons		6 persons	
ON LAND	4 persons		4 persons		4 persons	
ON WATER	2 persons		2 persons		2 persons	
FUEL CAPACITY	7.1 US gallons (27 litres) See-through polyethylene fuel tank. 8 hours of operation ⁵					
SPEED⁶	22 mph / 35 km per hour		19 mph / 30 km per hour		20 mph / 32 km per hour	
ON LAND	3.5 mph / 5 km per hour		3.5 mph / 5 km per hour		2.5 mph / 4 km per hour	
ON WATER⁷	3.5 mph / 5 km per hour		3.5 mph / 5 km per hour		2.5 mph / 4 km per hour	
SHIPPING WEIGHT	850 lbs / 386 kg	900 lbs / 408 kg	1050 lbs / 476 kg	1250 lbs / 570 kg	1260 lbs / 571 kg	1410 lbs / 641 kg
AXLE BEARING EXTENSIONS	Front - Optional Rear - N/A	Front - Standard Rear - Standard	Front - Standard Rear - Optional	Front - Standard Rear - Standard	Front - Standard Rear - Standard	
LCD DIGITAL GAUGE CLUSTER	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights			Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Engine Coolant Temperature, Low Oil Pressure and Parking Brake Reminder Lights (ARGO 8x8 750 HDi also features a Check Engine Light)		
TIRES	ARGO AT189 24x10.00-8NHS	ARGO AT189 24x10.00-8NHS	ARGO AT189 24x10.00-8NHS	ARGO AT189 25x12.00-9 NHS	ARGO AT189 25x12.00-9 NHS	
GROUND PRESSURE	2.1 psi (14.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks					
GROUND CLEARANCE	9.5" (240 mm)		9" (230 mm)		9.5" (240 mm)	
TIRES	10.5" (265 mm)		10" (255 mm)		10.5" (265 mm)	
TRACKS	10.5" (265 mm)		10.5" (265 mm)		10.5" (265 mm)	
OPERATING CONDITIONS	All weather, all terrain, -40°C to +40°C					

- Capacity includes occupants, cargo, outboard motor and fuel, and installed accessories. Max. outboard motor size 7.4 kW (9.9 hp).
- Total payload is 700lbs with max. 140lbs allocated to rear compartment.
- Towing capacity is approximate and depends on type of surface, load on vehicle as well as incline. Max Hitch Tongue Load (when equipped with hitch) 100 lbs / 45kg for all models
- Subject to rear compartment load capacity limitations.
- Fuel consumption depends on load and operating conditions.
- All speeds are approximate and depend on conditions.
- Always wear approved Personal Floatation Device (PFD) when operating in water or on ice.

Appearance and specifications subject to change without notice.

AVAILABLE ARGO COLORS

*Colors in this brochure are reproduced with great care, but may vary slightly from actual ARGO vehicle colors.



Optional hot-dip galvanizing for metal components for rust prevention.

COLOR OPTIONS FOR ALL STEEL PARTS

