

6x6 Frontier 650HD Specifications

Engine	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter, 2 year warranty
Model	Briggs & Stratton Vanguard
Horsepower	23
Displacement	627cc
Cooling	Air cooled
Starting	Electric/Recoil
Brakes	Hydraulic
Steering	One-piece ergonomic handlebar steering control with mounted brake lever. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.
Controls	Right-hand twist grip throttle and dash mounted choke control. Light switch and ignition switch.
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission	ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.
Drive System	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greaseable and are protected with double-sealed outer flange assemblies.
Frame	Formed steel channel construction, welded for high strength and durability. Polyester powder coated for lasting protection.
Body	Vacuum formed High Molecular Weight Polyethylene
Full Skid Plate	Standard
Load Capacity - On Land	700 lbs/ 317 kg total
Load Capacity - Rear Compartment	140 lbs / 63kg max.
Load Capacity - On Water	500 lbs / 227 kg total
Towing Capacity	1400 lbs/635 kg
Seating Capacity	4 persons on land, 2 persons on water

Fuel Capacity	7.1 US Gallons (27 litres) See through polyethylene fuel tank. 8 hours of operation based on load and operating conditions.
Speed (on land)	22 mph / 35 km per hour
Speed (on water)	3.5 mph / 5 km per hour
Shipping Weight	900 lbs / 408 kg
Axle Bearing Extensions	Front and Rear Standard
LCD Digital Gauge Cluster	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights
Tire	Argo 24 x 10.00-8 NHS
Ground Pressure	2.1 psi (14.5 kPa) using tires, 0.67 psi (4.6 kPa) using tracks
Ground Clearance Tires	9.5 inches - 240 mm
Ground Clearance Tracks	10.5 inches - 265 mm
Operating Conditions	All weather,all-terrain,-40°C to +40°C

Dimensions

