

8x8 Frontier 650 Specifications

| | |
|----------------------------------|--|
| Engine | 4 cycle OHV V-Twin gasoline engine,electronic ignition,full pressure lubrication and oil filter 2 year warranty |
| Model | Briggs & Stratton Vanguard |
| Horsepower | 23 |
| Displacement | 627 cc |
| Cooling | Air Cooled |
| Starting | Electric/Recoil |
| Brakes | Mechanical |
| Steering | One piece ergonomic handlebar steering control with mounted brake lever. For safety and ease handling, the ARGO steering transmission provides continuous torque to all axles. |
| Controls | Right-hand twist grip throttle and dash-mounted choke control. Light switch and ignition switch. |
| Clutch | Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission. |
| Transmission | Planetary differential transmission with High and Low range; Forward, Neutral, Reverse. |
| Drive System | Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greasable. |
| Frame | Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection |
| Body | Vacuum formed High Molecular Weight Polyethelene |
| Full Skid Plate | Optional |
| Load Capacity - On Land | 1000 lbs / 454 kg |
| Load Capacity - Rear Compartment | no restrictions |
| Load Capacity - On Water | 900 lbs / 408 kg |
| Towing Capacity | 1400 lbs / 635 kg |
| Seating Capacity - On Land | 6 persons |
| Seating Capacity - On Water | 4 persons |
| Fuel Capacity | 7.1 US Gallons (27 litres) See through polyethylene fuel tank. 8 hours of operation based on load and operating conditions. |

| | |
|---------------------------|---|
| Speed - On Land | 19 mph / 30 km per hour |
| Speed - On Water | 2.5 mph / 4 km per hour |
| Shipping Weight | 1050 lbs / 476 kg |
| Axle Bearing Extensions | Front - Standard....Rear - Optional |
| LCD Digital Gauge Cluster | Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights |
| Tires | ARGO AT189 24 x 10.00-8NHS |
| Ground Pressure | 2.1 psi (14.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks |
| Ground Clearance - Tires | 9" (230 mm) |
| Ground Clearance - Tracks | 10" (255 mm) |
| Operating Conditions | All weather, all terrain, -40C to +40C |
| Dimensions | <p>The image contains two technical drawings of a vehicle. The top drawing is a side view showing a four-wheeled vehicle with a canopy. Dimensions include a height of 46 in. (117 cm) at the front, 42-1/2 in. (108 cm) at the rear, and a wheelbase of 79 in. (201 cm). The bottom drawing is a top-down view showing the vehicle's footprint. Dimensions include an overall width of 60 in. (152 cm), an overall length of 119 in. (302 cm), a front compartment width of 43 in. (109 cm), and a rear compartment width of 30-1/2 in. (77 cm).</p> |