

8x8 Argo 750 HDI *Special Edition* Spec's

Engine	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter. 3 year limited Kohler warranty
Model	Kohler Aegis LH775
Horsepower	31
Displacement	748cc
Cooling	Liquid Cooled
Starting	Electric
Brakes	Hydraulic
Steering	One-piece ergonomic handlebar steering control with mounted brake lever. For safety and ease handling, the ARGO steering transmission provides continues torque to all axles
Controls	Right-hand twist grip throttle control assembly including light, signal and horn switches, dash mounted ignition switch
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission	ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.
Drive System	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greasable.
Frame	Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection.
Body	Vacuum formed High Molecular Weight Polyethylene.
Full Skid Plate	Standard
Load Capacity - On Land	454 kg (1000lbs) total
Load Capacity - On Water	386 kg (850 lbs) total
Towing Capacity	818 kg (1800 lbs)
Seating Capacity - On Land	6 persons
Seating Capacity - On Water	4 persons
Fuel Capacity	27 litres. See-through polyethylene fuel tank. 8 hours of operation.
Speed - On Land	32 km/h / 20 mph

Speed- On Water	4 km/h (5.5 km/h with ARGO AT189 tires)
Shipping Weight	1260 lbs (571Kg)
Axle Bearing Extentions	Front - Standard Rear - Standard
LCD Digital Gauge Cluster	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Engine Coolant Temperature, Low Oil Pressure, Parking Brake Reminder lights and Check Engine Light.
Tires	ARGO 25x12.00-9 NHS
Ground Pressure - Tires	14.5 kPa
Ground Pressure - Tracks	4.6 kPa
Ground Clearance - Tires	240 mm (9.5")
Ground Clearance - Tracks	265 mm (10.5")
Operating Conditions	All weather, all terrain, -40C to +40C
Dimensions	<p>ADJUSTABLE BUCKET SEATS: Weight adjustment: 50-120 kg Fore & aft adjustment: 160 mm Height adjustment: 60 mm Suspension travel: 70 mm</p> <p>SUPER TRACK: Adds 1 in. (25mm) to vehicle height RUBBER TRACK: Adds 1-1/4 in. (32mm) to vehicle height CONV. TOP: 1-1/2 in. (38mm) less than ROPS height.</p>

