

## Argo 8x8 Avenger 750 EFI Features

- Contoured dash design and premium padded bench seat
- Power to all wheels for optimal performance in challenging terrain
- One-piece ergonomic handlebar steering control
- State-of-the-art automatic continuous variable transmission with high and low range forward and reverse
- Excellent approach and departure angles to easily overcome obstacles
- Innovative design and space for up to 6 passengers
- Low emissions which meet both EPA and CARB standards
- Three-year limited engine warranty
- Load capacity of up to 1150 lbs on land or 1000 lbs on water

## Argo 8x8 Avenger 750 EFI Standard Equipment

- LCD Digital Gauge Cluster\* (Speedometer, tachometer, odometer, voltmeter, engine coolant temperature, plus low oil pressure and parking brake reminder lights) \*Avenger 750 EFI features an additional check engine light
- NEW 25" ARGO tires for optimum traction, smooth ride and better water performance
- Hydraulic vented disk brakes for ease of operation
- Independent emergency, parking brake
- Full skid plate for lower body protection
- Front & rear axle bearing extensions for increased axle and bearing life
- Convenience Group (12 volt outlet, cup holders, grab handle)

## Argo 8x8 Avenger 750 EFI Specifications

Engine	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter. 3 year warranty
Model	Kohler Aegis LH 775
Horsepower	31
Displacement	748 cc
Cooling	Liquid Cooled
Starting	Electric
Brakes	Hydraulic
Steering	One-piece ergonomic handlebar steering control with mounted brake lever. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.
Controls	Right hand twist grip throttle. Light switch and ignition switch.
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission	Planetary differential transmission with High and Low range; Forward, Neutral, Reverse.
Drive System	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greasable.
Frame	Formed steel channel construction, welded for high strength and durability. Polyester powder coated for lasing protection
Body	Vacuum formed High Molecular Weight Polyethylene
Full Skid Plate	Standard
Load Capacity - On Land	1150 lbs / 521 kg
Load Capacity - Rear Compartment	No restrictions
Load Capacity - On Water	1000 lbs / 454 kg
Towing Capacity	1800 lbs / 818 kg
Seating Capacity - On Land	6 persons
Seating Capacity - On Water	4 persons
Fuel Capacity	7.1 US Gallons (27 litres) See through polyethylene fuel tank. 8 hours of operation.
Speed - On Land	20 mph / 32 km per hour

Speed - On Water	2.5 mph / 4 km per hour
Shipping Weight	1250 lbs / 570 kg
Axle Bearing Extensions	Front - Standard...Rear - Standard
LCD Digital Gauge Cluster	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Engine Coolant Temperature, Low Oil Pressure, Parking Brake Reminder Lights and Check Engine Light
Tires	ARGO AT189 25x12.00-9 NHS
Ground Pressure	2.1 psi (14.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks
Ground Clearance Tires	9.5" (240 mm)
Ground Clearance Tracks	10.5" (265 mm)
Operating Conditions	All weather, all terrain, -40C to +40C

Dimensions

