

Argo 8x8 Frontier 650 Features

- Premium padded bench seat
- One-piece ergonomic handlebar steering control
- All-wheel traction with low center of gravity for extra stability
- State-of-the-art automatic continuously variable transmission with high and low range forward and reverse
- Low emissions
- Two-year limited engine warranty

Argo 8x8 Frontier 650 Standard Equipment

- LCD Digital Gauge Cluster (Speedometer, odometer, hourmeter, voltmeter, plus low oil pressure and parking brake reminder lights)
- Purpose designed 24" ARGO tires with special tread design
- Hydraulic vented disc brakes
- Emergency, parking brake
- Back-up Recoil starter
- Electronic ignition

Argo 8x8 Frontier 650 Specifications

Engine	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter 2 year warranty
Model	Briggs & Stratton Vanguard
Horsepower	23
Displacement	627 cc
Cooling	Air Cooled
Starting	Electric/Recoil
Brakes	Hydraulic
Steering	One piece ergonomic handlebar steering control with mounted brake lever. For safety and ease handling, the ARGO steering transmission provides continuous torque to all axles.
Controls	Right-hand twist grip throttle and dash-mounted choke control. Light switch and ignition switch.
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission	Planetary differential transmission with High and Low range; Forward, Neutral, Reverse.
Drive System	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greasable.
Frame	Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection
Body	Vacuum formed High Molecular Weight Polyethelene
Full Skid Plate	Optional
Load Capacity - On Land	1000 lbs / 454 kg
Load Capacity - Rear Compartment	no restrictions
Load Capacity - On Water	900 lbs / 408 kg
Towing Capacity	1400 lbs / 635 kg
Seating Capacity - On Land	6 persons
Seating Capacity - On Water	4 persons
Fuel Capacity	7.1 US Gallons (27 litres) See through polyethylene fuel tank. 8 hours of operation based on load and operating conditions.
Speed - On Land	19 mph / 30 km per hour
Speed - On Water	2.5 mph / 4 km per hour
Shipping Weight	1050 lbs / 476 kg
Axle Bearing Extensions	Front - Standard....Rear - Optional
LCD Digital Gauge	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights

Cluster	
Tires	ARGO AT189 24 x 10.00-8NHS
Ground Pressure	2.1 psi (14.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks
Ground Clearance - Tires	9" (230 mm)
Ground Clearance - Tracks	10" (255 mm)
Operating Conditions	All weather, all terrain, -40C to +40C
Dimensions	<p>The image contains two technical drawings of a vehicle. The top drawing is a side view showing a vehicle with four large tires. Dimensions include a height of 46 in. (117 cm) at the front, 42-1/2 in. (108 cm) at the rear, and a wheelbase of 79 in. (201 cm). The bottom drawing is a top-down view showing the vehicle's footprint. Dimensions include an overall width of 60 in. (152 cm), an overall length of 119 in. (302 cm), a front track width of 43 in. (109 cm), and a rear track width of 30-1/2 in. (77 cm).</p>