

## Argo 8x8 HDi 750 Features

- Contoured dash design and premium padded bench seat
- Power to all wheels for optimal performance in challenging terrain
- One-piece ergonomic handlebar steering control
- State-of-the-art automatic continuous variable transmission with high and low range forward and reverse
- Excellent approach and departure angles to easily overcome obstacles
- Innovative design and space for up to 6 passengers
- Low emissions which meet both EPA and CARB standards
- Three-year limited engine warranty
- Load capacity of up to 1150 lbs on land or 1000 lbs on water

## Argo 8x8 HDi 750 Standard Equipment

- LCD Digital Gauge Cluster\* (Speedometer, tachometer, odometer, voltmeter, engine coolant temperature, plus low oil pressure and parking brake reminder lights) \*Avenger 750 EFI features an additional check engine light
- NEW 25" ARGO tires for optimum traction, smooth ride and better water performance
- Hydraulic vented disk brakes for ease of operation
- Independent emergency, parking brake
- Full skid plate for lower body protection
- Front & rear axle bearing extensions for increased axle and bearing life
- Convenience Group (12 volt outlet, cup holders, grab handle)

## Argo 8x8 HDi 750 Specifications

Engine	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter. 3 year warranty
Model	Kohler Aegis LH775
Horsepower	31
Displacement	748cc
Cooling	Liquid Cooled
Starting	Electric
Brakes	Hydraulic
Steering	One-piece ergonomic handlebar steering control with mounted brake lever. For safety and ease handling, the ARGO steering transmission provide continuous torque to all axles
Controls	Right-hand twist grip throttle grip and dash-mounted choke control. Light switch and ignition switch.
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission	ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.
Drive System	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greasable.
Frame	Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection.
Body	Vacuum formed High Molecular Weight Polyethylene.
Full Skid Plate	Standard
Load Capacity - On Land	1150 lbs / 521 kg total
Load Capacity - Rear Compartment	No restrictions
Load Capacity - On Water	1000 lbs / 454 kg total
Towing Capacity	1800 lbs / 818 kg
Seating Capacity - On Land	6 persons
Seating Capacity - On Water	4 persons
Fuel Capacity	7.1 Us gallons (27 litres) See-through polyethylene fuel tank. 8 hours of operation.
Speed - On Land	20 mph / 32 km per hour
Speed- On Water	2.5 mph / 4 per hour

Shipping Weight	1250 lbs / 570 kg
Axle Bearing Extentions	Front - Standard Rear - Standard
LCD Digital Gauge Cluster	Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Engine Coolant Temperature, Low Oil Pressure, Parking Brake Reminder lights and Check Engine Light.
Tires	ARGO AT189 25x12.00-9 NHS
Ground Pressure	2.1 psi (14.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks
Ground Clearance - Tires	9.5" (240 mm)
Ground Clearance - Tracks	10.5" (265 mm)
Operating Conditions	All weather, all terrain, -40C to +40C